

Revision Date: 03.01.23

# Del-Val

DELIVERING VALUE

## DEL-VAL 110 FIBERED ROOF COATING

### DESCRIPTION

Del-Val 110 Fibered Roof Coating is a fiber reinforced asphalt roof coating that provides a durable watertight barrier over existing roof surfaces.

### USES

Del-Val 110 Fibered Roof Coating may be used on smooth surface BUR, or SBS and APP bituminous membranes, metal surfaces, roll-roofing. **DO NOT USE with TPO, EPDM, PVC or other single-ply membranes.**

### PREPARATION

All surfaces must be clean and free of any oil, grease, dirt and all other foreign matter. Repair all holes, cracks, blisters, tears or breaks by spreading Del-Val 211 Flashing Cement over damaged area then embed United Asphalt Cotton or Fiberglass fabric.

### APPLICATION

Apply to a clean dry surface using a brush or squeegee. For best results weather should be clear with no threat of rain for 48 hours.

### COVERAGE

Apply at the rate of approximately 4 gallons per 100 sq. ft. Must stir coating before using.

### CLEANUP

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.


### CODE APPROVALS/COMPLIANCE

This product meets or exceeds the requirements of ASTM D 4479 Type I

**LEARN MORE**  [UnitedAsphalt.com/DV110](https://www.unitedasphalt.com/DV110)



### TOOLS NEEDED



### PACKAGING SIZES

