

Revision Date: 03.01.23

Del-Val

DELIVERING VALUE

DEL-VAL 111 NON-FIBERED ROOF COATING

DESCRIPTION

Del-Val 111 Non-Fibered Roof Coating is a non-fibrated asphalt coating that is used to prevent moisture penetrating through foundation walls and protecting a variety of roof surfaces. After the product is applied it forms a smooth flexible shell that helps resist the entrance of moisture through foundation walls. On the roof Del-Val 111 Non-Fibered Roof Coating forms a weather resistant film that has excellent adhesion to most roof surfaces.

USES

Del-Val 111 Non-Fibered Roof Coating is used for exterior below-grade masonry and block walls where no hydrostatic pressure is present. It is used for coating all types of smooth surface asphalt roofs and can also be used to protect wood and metal above or below-grade.

PREPARATION

All surfaces must be clean and free of any oil, grease, dirt and all other foreign matter. Must stir coating before using.

APPLICATION

Can be applied using: brush, roller or heavy duty spray equipment. Allow 24 hours drying time before backfilling against the foundation walls. Do not apply over wet/damp or frost covered surfaces.

COVERAGE

Roofing Surfaces (smooth asphalt surfaces): Apply at the rate of approximately 1 to 2 gallons per 100 sq.ft.

CLEANUP

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.


CODE APPROVALS/COMPLIANCE

This product meets or exceeds the requirements of ASTM D449-83 Type I & ASTM D-4479 Type I

LEARN MORE  [UnitedAsphalt.com/DV111](https://www.UnitedAsphalt.com/DV111)



TOOLS NEEDED



PACKAGING SIZES

