

Revision Date: 03.01.23

Del-Val

DELIVERING VALUE

DEL-VAL 120 FIBERED EMULSION COATING

DESCRIPTION

Del-Val 120 Fibered Emulsion Coating is a fiber reinforced asphalt based clay emulsion coating designed for both brush and spray applications on a variety of roof substrates. This product has excellent resistance to water and cures to a tough durable finish.

USES

Del-Val 120 Fibered Emulsion Coating may be used on smooth surfaces BUR, SBS, APP bituminous membranes, metal surfaces, and roll-roofing. It can also be used for damp-proofing above and below-grade foundation walls and masonry surfaces.

PREPARATION

All surfaces must be clean and free of any oil, grease, dirt and all other foreign matter. Repair all holes, cracks, blisters, tears or breaks by spreading Del-Val Flashing Cement over damaged area then embed United Asphalt Cotton or Fiberglass Fabric.

APPLICATION

Apply to a clean surface using a brush or squeegee. For best results weather should be clear with no threat of rain for 48 hours.

COVERAGE

Apply at the rate of approximately 3 gallons per 100 sq. ft. Must stir coating before using.

CLEANUP

Clean tools with warm water and soap.


CODE APPROVALS/COMPLIANCE

This product meets or exceeds the requirements of ASTM D 1227-87 Type IV

LEARN MORE  UnitedAsphalt.com/DV120



TOOLS NEEDED



PACKAGING SIZES

