

Revision Date: 03.01.23

Del-Val

DELIVERING VALUE

DEL-VAL 241 SILICONE ROOF PATCH (WHITE, BLACK & GRAY)

DESCRIPTION

Del-Val 241 Silicone Roof Patch is a one-part, high solids, low VOC silicone elastomeric flashing mastic specifically designed for use in sealing roof penetrations, seams, curbs, flashings, and other areas on the roof where water infiltration is possible. It works well on roofs that were previously coated with Del-Val 320 Silicone Coating. Once cured, this liquid applied silicone mastic provides a durable, seamless, flexible, waterproof membrane that resists lateral movement, shear and will allow for normal expansion and contraction.

USES

Del-Val 241 Silicone Roof Patch provides a protective barrier for multiple applications where water infiltrates a roofing system. The most common areas include seams, pipe boots, curbs, flashing details, penetrations, and exposed fasteners.

PREPARATION

Surface must be clean, free of all loose particles, dirt debris and other contaminants that could inhibit adhesion. For best results, ambient temperature should be between 50–90°F. Higher temperatures will shorten the cure time and working time. Lower temperatures will lengthen the skin over, tack free and ultimate cure time.

APPLICATION AND COVERAGE RATE

Brush apply Del-Val 241 Silicone Roof Patch at a rate of 100 linear feet per gallon over a seam at 4" wide achieving 40 mils wet. Minimum mil thickness 25 wet mils & Maximum 50 wet mils. Tack free in 1–2 hours. Cure time is 12–18 hours.

LIMITATIONS AND PRECAUTIONS

Shelf Life is 18 months stored indoors at 50–85°F. Avoid contamination in sealed containers. Store away from heat, sources of ignition and incompatibles. Use only in well ventilated areas. Refer to SDS for more information.

LEARN MORE [→ UnitedAsphalt.com/DV241](https://www.unitedasphalt.com/DV241)



TOOLS NEEDED ▼



PACKAGING SIZES ▼

