

Revision Date: 03.01.23

# Del-Val

DELIVERING VALUE

## DEL-VAL 300 SILVER SEAL FIBERED ALUMINUM COATING

### DESCRIPTION

Del-Val 300 Silver Seal Fibered Aluminum Coating is a protective metallic shield that extends the life of asphalt and metal roof surfaces. Del-Val 300 Silver Seal Fibered Aluminum Coating reflective surface protects the roof's surface from destructive overheating and actinic deterioration.

### PREPARATION

Prepare the roof surface by sweeping clean any dust, dirt or debris. Use a wire brush to remove rust from metal. Roof surface must be oil free and free of moisture both on and beneath the surface. Repair all holes, cracks, blisters, tears or breaks by spreading Flashing Cement over damaged area then embed Cotton or Fiberglass fabric. Allow repairs to cure 60 days before coating.

### APPLICATION

Apply Del-Val 300 Silver Seal Fibered Aluminum Coating with a soft bristled brush, paint roller or heavy duty spray equipment. Product should be mechanically mixed before applying. Spread the product uniformly over the roof surface.

### COVERAGE AND DRY TIME

Apply at the rate of 1 to 1.5 gallons per 100 sq. ft.

### CLEANUP

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.


### CODE APPROVALS/COMPLIANCE

This product meets or exceeds the requirements of ASTM D-2824 Type III

**LEARN MORE** [→ UnitedAsphalt.com/DV300](https://www.unitedasphalt.com/DV300)



### TOOLS NEEDED ∨



### PACKAGING SIZES ∨



### PRECAUTIONS

Del-Val 300 should not be applied if dew is present, roof is at all wet, impending moisture is expected within 24 hours or where ponding water is present. Any of these conditions will have an adverse effect on the performance of the product.