

Revision Date: 03.01.23

# Del-Val

DELIVERING VALUE

## DEL-VAL 401 FIBERED FOUNDATION COATING

### DESCRIPTION

Del-Val 401 Fibered Foundation Coating is a fibrated asphalt coating that is used to prevent moisture penetration through foundation wall surfaces. After the product is applied it forms a fiber reinforced shell that helps resist the entrance of moisture through foundation walls.

### USES

Del-Val 401 Fibered Foundation Coating is used for exterior below-grade masonry and block walls where no hydrostatic pressure is present.

### PREPARATION

All surfaces must be clean and free of any oil, grease, dirt and all other foreign matter. Must stir coating before using.

### APPLICATION

Can be applied using: brush or roller. Allow 24 hours drying time before backfilling against the foundation walls. Do not apply over wet/damp or frost covered surfaces.

### COVERAGE

**Masonry Surfaces:** apply at the rate of approximately 1 to 1.5 gallons per 100 sq. ft.

### CLEANUP

Clean tools with Del-Val Orange Cleaner & Degreaser, taking necessary precautions when handling combustible liquids.

### PRECAUTION

DO NOT THIN. DO NOT HEAT CONTAINER. DO NOT store in an area where temperatures exceed 120°F


### CODE APPROVALS/COMPLIANCE

This product meets or exceeds the requirements of ASTM D4479 Type I

**LEARN MORE**  [UnitedAsphalt.com/DV401](https://www.unitedasphalt.com/DV401)



### TOOLS NEEDED



### PACKAGING SIZES

