

Revision Date: 03.01.23



DEL-VAL 501 RC 70 TACK COAT

DESCRIPTION

Del-Val 501 RC 70 Tack Coat is an asphalt based cut-back product used for priming and bonding of asphalt surfaces. Del-Val 501 RC 70 Tack Coat is formulated with refined asphalts and is cut with 105°F flash point mineral spirits to a smooth consistency.

USES

Del-Val 501 RC 70 Tack Coat can be used as a prime coat on asphalt surfaces before overlaying new asphalt surfaces.

APPLICATION

Apply with a brush or spray equipment on a dry and clean surface. Surface must be dry and clean before applying.

COVERAGE


Approximately 150 sq. ft. per gallon.

PRECAUTION

DO NOT HEAT MATERIAL. **DANGER: COMBUSTIBLE MIXTURE.** USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED.



TOOLS NEEDED ▾



PACKAGING SIZES ▾



LEARN MORE ↓

UnitedAsphalt.com/DV501

PHYSICAL PROPERTIES

Color	Dark Brown-Black
Total Solids	65% to 70% wt
Solvent Content	30% to 35% wt
Solvent Type	Mineral Spirits
Flash Point	105° F
Viscosity	70 - 140 cSt @ 140°F
Wt/Gal	7.75 lbs

BASE ASPHALT

Softening Point	115° - 130° F
Penetration	60 - 110

CODE APPROVALS/COMPLIANCE

Meets: ASTM D-2028 and ASSHTO M81 Specifications